

View Online at <https://aerobasegroup.com/nsn/5305-00-577-5434>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.845 inches and 0.875 inches

**Fastener Length:**

Between 2.350 inches and 2.370 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.977 inches and 1.000 inches

**Head Height:**

Between 0.490 inches and 0.500 inches

**Shoulder Diameter:**

0.746 inches first shoulder and 0.748 inches first shoulder

**Shoulder Length:**

1.495 inches first shoulder and 1.505 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.750 inches

**Width Across Flats:**

0.375 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0