

View Online at <https://aerobasegroup.com/nsn/5305-00-579-1012>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.455 inches

**Fastener Length:**

0.640 inches

**Head Style:**

Fillister

**Head Diameter:**

0.414 inches

**Head Height:**

0.237 inches

**Hole Diameter:**

0.064 inches

**Shank Unthreaded Hole Diameter:**

0.062 inches first hole

**First Diameter From Head:**

0.250 inches

**Second Diameter From Head:**

0.158 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.455 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.640 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Hole Configuration Style:**

Round longitudinal hole

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.062 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 1010

**Material Specification:**

Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0