

View Online at <https://aerobasegroup.com/nsn/5305-00-579-1012>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.455 inches

Fastener Length:

0.640 inches

Head Style:

Fillister

Head Diameter:

0.414 inches

Head Height:

0.237 inches

Hole Diameter:

0.064 inches

Shank Unthreaded Hole Diameter:

0.062 inches first hole

First Diameter From Head:

0.250 inches

Second Diameter From Head:

0.158 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.455 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.640 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

60000 pounds per square inch

Hole Configuration Style:

Round longitudinal hole

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.062 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 1010

Material Specification:

Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0