NSN 5305-00-579-1267

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-579-1267

| Three d Clares |
|--|
| Thread Class: |
| 2a The a LDC of the state of th |
| Thread Direction: |
| Right-hand Three did no of the |
| Thread Length: |
| Between 0.152 inches and 0.188 inches |
| Fastener Length: |
| Between 0.156 inches and 0.188 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.187 inches and 0.205 inches |
| Head Height: |
| Between 0.081 inches and 0.088 inches |
| Hole Diameter: |
| 0.046 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.125 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 60000 pounds per square inch |
| Screw Material: |
| Steel or steel comp 1010 |
| Screw Material Specification: |
| Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal |
| specification 2nd material response |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round longitudinal hole |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-00-579-1267

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0