NSN 5305-00-579-1449

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-579-1449 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.375 inches and 0.500 inches |
| Fastener Length: |
| 0.880 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| 0.313 inches |
| Head Height: |
| 0.170 inches |
| Hole Diameter: |
| 0.047 inches |
| First Diameter From Head: |
| 0.180 inches |
| Second Diameter From Head: |
| 0.186 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.030 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.500 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Hole Configuration Style: |
| Round |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| |

Material:

Steel comp 416

NSN 5305-00-579-1449

Externally Relieved Body Screw - Page 2 of 2



| Material Specification: |
|---|
| Aisi assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0