## NSN 5305-00-579-2232

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-579-2232 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.375 inches and 1.500 inches **Fastener Length:** Between 1.440 inches and 1.500 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** -1I-s-6050sjgcams 6300 military specification 1st material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas603 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-579-2232

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

spec.