## NSN 5305-00-579-2234



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-579-2234 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 2.160 inches and 2.250 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** -1I-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium Qq-p-416, type 1, cl 3 federal specification single treatment response

Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment

Thread Series Designator:

Unjf

Specification Data:

80205-nas603 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

-
Demilitarization:

No

## NSN 5305-00-579-2234

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

spec.