## NSN 5305-00-579-3062

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-579-3062 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.310 inches and 0.370 inches **Fastener Length:** 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** 0.310 inches **Head Height:** 0.060 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** 0.217 inches **Third Diameter From Head:** 0.160 inches **Fourth Diameter From Head:** 0.187 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.050 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.255 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.380 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** 16.0 microinches on second dia. And 32.0 microinches on forth dia

Material:

Steel comp 416

**Material Specification:** 

Aisi assn standard single material response

## NSN 5305-00-579-3062

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0