## NSN 5305-00-579-4700

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-579-4700

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.828 inches
Fastener Length:
1.375 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
160000 pounds per square inch  Hardness Rating:  36.0 rockwell c
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660
160000 pounds per square inch Hardness Rating: 36.0 rockwell c Screw Material: Iron alloy 660 Screw Material Specification:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium  Thread Series Designator:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium Thread Series Designator: Unc
160000 pounds per square inch Hardness Rating: 36.0 rockwell c Screw Material: Iron alloy 660 Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium  Thread Series Designator: Unc Shelf Life: N/a
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium  Thread Series Designator: Unc Shelf Life: N/a
160000 pounds per square inch Hardness Rating: 36.0 rockwell c Screw Material: Iron alloy 660 Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c  Screw Material: Iron alloy 660  Screw Material Specification: Ams 5735 assn standard single material response Screw Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: