NSN 5305-00-580-6232

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-580-6232 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.441 inches and 0.508 inches **Fastener Length:** Between 1.826 inches and 1.873 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:**

Mac ps13145, type 2, cl 3, fscm 88277 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-580-6232

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0