NSN 5305-00-580-6232

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-580-6232

Thread Class:
3a Thread Direction:
Right-hand
Thread Length: Between 0.441 inches and 0.508 inches
Fastener Length:
Pastener Length: Between 1.826 inches and 1.873 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.625 inches and 0.635 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
High-torque Thread Diameter:
0.312 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi):
24 Min Tanaila Strongth (noi):
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mac ps13145, type 2, cl 3, fscm 88277 mfr ref single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-580-6232

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

