NSN 5305-00-580-6339

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-580-6339 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.283 inches and 0.333 inches **Fastener Length:** Between 0.481 inches and 0.511 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.244 inches and 0.279 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049rjgcams 6322 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No **Fiig:**

A003b0

NSN 5305-00-580-6339

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.