NSN 5305-00-580-7531

Machine Screw - Page 1 of 2

Thread Class:

Thread Direction:

3a

View Online at https://aerobasegroup.com/nsn/5305-00-580-7531



Right-hand Thread Length: Between 0.589 inches and 0.690 inches Fastener Length: Between 0.660 inches and 0.690 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Screw Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas604 professional/industrial association standard Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No

NSN 5305-00-580-7531

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

