

View Online at <https://aerobasegroup.com/nsn/5305-00-582-5808>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.563 inches and 0.625 inches

Fastener Length:

0.625 inches

Head Style:

Fillister

Head Diameter:

Between 0.208 inches and 0.226 inches

Head Height:

Between 0.089 inches and 0.096 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1524 or steel comp 1025 or steel comp 1527 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1038 or steel comp 1040 or steel comp 1541 or steel comp 1108 or steel comp 1109 or steel comp 1110

Screw Material Specification:

Qq-s-633 federal specification single material response

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0