Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-582-5850

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.844 inches |
| Fastener Length: |
| 1.781 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.172 inches and 0.203 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| 0.047 inches |
| First Diameter From Head: |
| Between 0.145 inches and 0.148 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.938 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 2 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hole Configuration Style: |
| Hexagon flats |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp 1213 |
| Material Specification: |
| Aisi assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| |

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0