NSN 5305-00-582-8184



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-582-8184 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.281 inches and 0.286 inches **Fastener Length:** 0.437 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.432 inches and 0.437 inches **Head Height:** 0.125 inches **Shoulder Diameter:** 0.245 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.151 inches first shoulder and 0.156 inches first shoulder **Locking Feature:** Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 and steel comp 303se **Material Specification:** Astm a582 condition a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171 finish 5.4.1 military standard single treatment response **Thread Series Designator:** Unf Shelf Life:

Unit Of Measure:

N/a

NSN 5305-00-582-8184

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.