NSN 5305-00-583-5564



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-583-5564 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.280 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.131 inches and 0.136 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.314 inches and 0.345 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-583-5564

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.