## NSN 5305-00-584-7662

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-584-7662 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 4.113 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches **First Diameter From Head:** Between 0.158 inches and 0.164 inches **Second Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 3.406 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.625 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project **Special Features:** W/90 degree point on threaded end Material: Steel comp 430 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate** 

Unc

**Thread Series Designator:** 

## NSN 5305-00-584-7662

Externally Relieved Body Screw - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0