

View Online at <https://aerobasegroup.com/nsn/5305-00-584-8767>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.000 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.568 inches and 0.635 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 8630

**Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.