

View Online at <https://aerobasegroup.com/nsn/5305-00-587-7652>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.563 inches and 0.625 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 384

**Screw Material Specification:**

66 federal standard all material responses

**Screw Surface Treatment:**

Passivate

**Special Features:**

Pozidriv

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0