## NSN 5305-00-591-3388

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-591-3388 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.312 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.278 inches and 0.288 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.018 inches Material: Steel comp 1050 primary washer or steel comp 1060 primary washer **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** 

Unc

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-00-591-3388

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0