NSN 5305-00-596-7372

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-596-7372

| View Online at https://aerobasegroup.com/nsn/5305-00-596-7372 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.250 inches |
| Fastener Length: |
| 1.750 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.302 inches and 0.323 inches |
| Width Between Flats: |
| Between 0.736 inches and 0.750 inches |
| Thread Diameter: |
| 0.500 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 120000 pounds per square inch |
| Hardness Rating: |
| 25.0 rockwell c and 34.0 rockwell c |
| Criticality Code Justification: |
| Zzzy |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 5 assn standard single material response |
| Surface Treatment: |
| Chromium |
| Special Test Features: |
| Special quality control testing |
| Surface Treatment Specification: |
| Qq-c-320, cl2 federal specification single treatment response |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unf |
| Reference Number Differentiating Characteristics: |

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

N/a

Shelf Life:

NSN 5305-00-596-7372

Hexagon Head Cap Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0