

View Online at <https://aerobasegroup.com/nsn/5305-00-600-8993>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.327 inches and 0.357 inches

Fastener Length:

Between 0.660 inches and 0.690 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.740 inches and 0.760 inches

Head Height:

Between 0.333 inches and 0.368 inches

Shoulder Diameter:

0.615 inches first shoulder and 0.635 inches first shoulder

Shoulder Length:

0.240 inches first shoulder and 0.260 inches first shoulder

Shank Unthreaded Hole Diameter:

0.077 inches first hole and 0.087 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

38.0 rockwell c and 46.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.125 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Roove 0.083 in. Lg 0.369 in. Dia. And slot in thd end

Material:

Steel comp 4140

Surface Treatment:

Phosphate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0