## NSN 5305-00-600-8993



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-600-8993 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.327 inches and 0.357 inches **Fastener Length:** Between 0.660 inches and 0.690 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.740 inches and 0.760 inches **Head Height:** Between 0.333 inches and 0.368 inches **Shoulder Diameter:** 0.615 inches first shoulder and 0.635 inches first shoulder **Shoulder Length:** 0.240 inches first shoulder and 0.260 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.077 inches first hole and 0.087 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 38.0 rockwell c and 46.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.125 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** Roove 0.083 in. Lg 0.369 in. Dia. And slot in thd end Material: Steel comp 4140 **Surface Treatment:** Phosphate

**Thread Series Designator:** Unf Shelf Life: N/a

## NSN 5305-00-600-8993

Shoulder Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0