

View Online at <https://aerobasegroup.com/nsn/5305-00-601-8271>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.380 inches and 0.447 inches

**Fastener Length:**

Between 0.765 inches and 0.812 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.3765 inches and 0.3813 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches top of head

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130

**Surface Treatment:**

Cadmium and paint

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification 1st treatment response and ps 13421 fscm 76301 mfr ref 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0