NSN 5305-00-605-2398



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-605-2398 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.981 inches and 1.062 inches **Fastener Length:** Between 1.031 inches and 1.062 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.072 inches and 0.079 inches **Hole Diameter:** 0.037 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 8630 Qq-p-416, type 1, cl 3 federal specification single treatment response

Screw Material Specification: Mil-s-6050 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification: Head Hole Configuration Style:** Round **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-605-2398

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.