## NSN 5305-00-605-4092

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-605-4092

Thread	Class:

- 3a
- Thread Direction:
- **Right-hand**

## Thread Length:

0.330 inches

#### Fastener Length:

0.767 inches

#### Head Diameter:

0.375 inches

#### **Head Height:**

Between 0.290 inches and 0.300 inches

#### **Extended Washer Diameter:**

0.625 inches

#### **Extended Washer Thickness:**

0.098 inches

#### Shoulder Diameter:

0.625 inches first shoulder

#### Shoulder Length:

0.295 inches first shoulder

#### Internal Drive Style:

Slot

#### Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

#### Shoulder Shape:

Round first shoulder

#### **Special Features:**

Heat treat 125-145000 psi

#### Material:

Steel comp 8630 or steel comp 4130

#### Material Specification:

Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response

#### Thread Series Designator:

Unf

## Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# NSN 5305-00-605-4092

Shoulder Screw - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-6050 spec.

