NSN 5305-00-606-2906

Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-606-2906

| Thread Class: |
|---|
| a |
| Sa Thread Direction: |
| Right-hand |
| - |
| Thread Length: Between 0.553 inches and 0.695 inches |
| Fastener Length: |
| Between 3.490 inches and 3.510 inches |
| |
| Head Style: Flat chamfer |
| Head Diameter: |
| |
| Between 0.365 inches and 0.385 inches |
| Head Height: |
| Between 0.195 inches and 0.215 inches |
| Hole Diameter: |
| 0.047 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| Between 0.188 inches and 0.190 inches |
| Hole Quantity: |
| |
| |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 32.0 rockwell c and 36.0 rockwell c |
| Hole Configuration Style: |
| Round longitudinal hole |
| Surface Finish: |
| 63.0 microinches grip |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |

NSN 5305-00-606-2906

Socket Head Cap Screw - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

