NSN 5305-00-606-9526

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-606-9526

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.352 inches and 0.403 inches
Fastener Length:
Between 1.164 inches and 1.184 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.722 inches and 0.740 inches
Head Height:
Between 0.189 inches and 0.204 inches
Grip Diameter:
Between 0.3737 inches and 0.3742 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Internal Drive Style:
-
High-torque Thread Diameter:
0.375 inches
Grip Length:
Between 0.625 inches and 0.641 inches
Thready Qty Per Inch (tpi): 24
²⁴ Distance From Head Largest Bearing Surface To Shank Hole Center:
1.036 inches and 1.056 inches first hole
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Special Features: Retaining element in shank
Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

NSN 5305-00-606-9526

Close Tolerance Screw - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

