

View Online at <https://aerobasegroup.com/nsn/5305-00-606-9527>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.352 inches and 0.403 inches

**Fastener Length:**

Between 4.601 inches and 4.621 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.722 inches and 0.740 inches

**Head Height:**

Between 0.189 inches and 0.204 inches

**Grip Diameter:**

Between 0.3737 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches and 0.116 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 4.062 inches and 4.078 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.473 inches and 4.493 inches first hole

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Special Features:**

Retaining element in shank

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0