## NSN 5305-00-606-9527

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.352 inches and 0.403 inches Fastener Length: Between 4.601 inches and 4.621 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.722 inches and 0.740 inches **Head Height:** Between 0.189 inches and 0.204 inches **Grip Diameter:** Between 0.3737 inches and 0.3742 inches Shank Unthreaded Hole Diameter: 0.106 inches and 0.116 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Grip Length: Between 4.062 inches and 4.078 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 4.473 inches and 4.493 inches first hole Surface Finish: 32.0 microinches grip **Product Name:** Navy special project **Special Features:** Retaining element in shank Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-00-606-9527

Close Tolerance Screw - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

