## NSN 5305-00-608-7789

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-608-7789 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.252 inches and 0.282 inches **Fastener Length:** Between 0.343 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Secondary Washer Relationship To Primary Washer: Not identical **Secondary Washer Style: Primary Washer Outside Diameter:** 0.253 inches **Secondary Washer Outside Diameter:** 0.263 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.093 inches **Secondary Washer Material Thickness:** 0.019 inches Material: Copper alloy **Material Specification:** 

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

## NSN 5305-00-608-7789

Assembled Washer Screw - Page 2 of 2



Surface Treatment:
Tin
Thread Series Designator:
Unc
Specification Data:
80205-nas720 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0