

View Online at <https://aerobasegroup.com/nsn/5305-00-612-3659>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.293 inches and 0.328 inches

Fastener Length:

Between 1.418 inches and 1.438 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.449 inches and 0.502 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 1.110 inches and 1.125 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

40.0 rockwell c and 45.0 rockwell c

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.323 inches first hole and 1.343 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Retaining element in threads

Material:

Steel comp 8740 or steel comp e4340 or steel comp 4340

Surface Treatment:

Cadmium head and chromate head

Surface Treatment Specification:

Qq-p-416, ty2 cl3 federal specification single treatment response head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0