NSN 5305-00-612-8976

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-612-8976 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.430 inches and 0.490 inches **Fastener Length:** Between 0.850 inches and 0.870 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.312 inches and 0.313 inches **Head Height:** Between 0.480 inches and 0.500 inches **Grip Diameter:** Between 0.2490 inches and 0.2500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.360 inches and 0.440 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 33.0 rockwell c and 38.0 rockwell c Material: Steel comp 4140 **Material Specification:** Qq-b-624 federal specification single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232 ty z cl 1 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-612-8976

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.