NSN 5305-00-616-2052



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-616-2052 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.803 inches and 0.865 inches **Fastener Length:** Between 0.865 inches and 0.885 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.160 inches and 0.171 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b **Screw Material:** Steel **Screw Material Specification:** Ams 5061 assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:**

Unc Shelf Life:

N/a

NSN 5305-00-616-2052

Machine Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A500d0