

View Online at <https://aerobasegroup.com/nsn/5305-00-616-2377>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.298 inches and 0.453 inches

Fastener Length:

Between 0.844 inches and 0.906 inches

Head Style:

Round extended washer

Head Diameter:

Between 0.302 inches and 0.322 inches

Head Height:

Between 0.082 inches and 0.092 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.023 inches and 0.028 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Screw Material:

Steel comp 8630 or steel comp 4037

Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

Screw Surface Treatment:

Cadmium or zinc

Screw Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.