NSN 5305-00-616-2509

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-616-2509



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.666 inches and 0.829 inches Fastener Length: Between 0.844 inches and 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.161 inches and 0.170 inches Hole Diameter: 0.062 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-00-616-2509

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

