NSN 5305-00-616-3800

Machine Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-00-616-3800



3a **Thread Direction: Right-hand Thread Length:** Between 0.189 inches and 0.301 inches Fastener Length: Between 0.761 inches and 0.791 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp 4037 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A500d0

NSN 5305-00-616-3800

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5626 spec.

