NSN 5305-00-616-6964

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-616-6964

Thread Class:
3a Thread Directions
Thread Direction:
Right-hand Thread Longth
Thread Length: Between 0.251 inches and 0.301 inches
Fastener Length: Between 0.511 inches and 0.541 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium or chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas1203 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-616-6964

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0