NSN 5305-00-616-8650

Machine Screw - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5305-00-616-8650



Thread Direction: Right-hand Thread Length: Between 0.469 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas604 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

NSN 5305-00-616-8650

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

