NSN 5305-00-619-4860

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-619-4860 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.151 inches and 0.158 inches **Fastener Length:** Between 0.433 inches and 0.439 inches **Head Style:** Flat chamfer **Head Diameter:** 0.438 inches **Head Height:** Between 0.139 inches and 0.146 inches **First Diameter From Head:** Between 0.228 inches and 0.233 inches **Second Diameter From Head:** 0.312 inches **Third Diameter From Head:** Between 0.223 inches and 0.227 inches **Fourth Diameter From Head:** Between 0.233 inches and 0.234 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.245 inches and 0.252 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.391 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.422 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4 Material: Steel

Unf

Thread Series Designator:

NSN 5305-00-619-4860

Externally Relieved Body Screw - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0