Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-619-4936

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.438 inches Fastener Length: 1.438 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification: Qe,s-763 federal specification single material response
Thread Direction: Right-hand Thread Length: 0.438 inches Fastener Length: 1.438 inches Head Style: Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Jumeter: 0.250 inches Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Jumeter:
Right-hand Thread Length: 0.438 inches Fastener Length: 1.438 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Thread Length: 0.438 inches Fastener Length: 1.438 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Viewed Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.438 inches Fastener Length: 1.438 inches Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.212 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Fastener Length: 1.438 inches Head Style: Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
1.438 inches Head Style: Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Second Diameter From Head: 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Head Style: Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Hexagon Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Head Height: 0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.188 inches Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Width Between Flats: 0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.500 inches First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
First Diameter From Head: 0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.260 inches Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Second Diameter From Head: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.812 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
0.250 inches Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Thready Qty Per Inch (tpi): 20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
20 Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Externally Relieved Body Diameter Quantity: 2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
2 Product Name: Navy special project Material: Steel comp 303 Material Specification:
Product Name: Navy special project Material: Steel comp 303 Material Specification:
Navy special project Material: Steel comp 303 Material Specification:
Material: Steel comp 303 Material Specification:
Steel comp 303 Material Specification:
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0