# NSN 5305-00-619-6022

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-619-6022



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.314 inches and 0.451 inches

#### Fastener Length:

Between 2.953 inches and 2.998 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.337 inches and 0.387 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp 8630

#### **Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-619-6022

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

