# NSN 5305-00-619-6301

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-619-6301



### Thread Class:

3a

**Thread Direction:** 

Right-hand

# Thread Length:

Between 0.291 inches and 0.341 inches

# Fastener Length:

Between 1.051 inches and 1.081 inches

# Head Style:

Pan

#### Head Diameter:

Between 0.473 inches and 0.492 inches

#### Head Height:

Between 0.162 inches and 0.175 inches

#### Internal Drive Style:

# Cross recess type 1

Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

# Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

#### Screw Surface Treatment:

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

# Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas623 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5305-00-619-6301

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

