## NSN 5305-00-620-3761

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-620-3761 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 1.281 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.625 inches **Head Height:** 0.141 inches **First Diameter From Head:** 0.359 inches **Second Diameter From Head:** 0.438 inches **Third Diameter From Head:** 0.156 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.282 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 **Special Features:** Second relieved threaded 7/16-20 unf 2a **Material Specification:** Astm a582 assn standard single material response

Oxide

**Surface Treatment:** 

**Surface Treatment Specification:** 

Mil-p-12011 gr 1 military specification single treatment response

## NSN 5305-00-620-3761

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-p-12011 spec.