## NSN 5305-00-623-0839

Shoulder Screw - Page 1 of 2





Thread Class:
3a There d Directions
Thread Direction:
Right-hand
Thread Length:
Between 0.382 inches and 0.432 inches
Fastener Length:
Between 1.454 inches and 1.484 inches
Head Style:
Flat countersunk Head Diameter:
Between 0.339 inches and 0.381 inches
Shoulder Diameter:         0.217 inches first shoulder and 0.218 inches first shoulder
Shoulder Length:
0.969 inches first shoulder and 0.989 inches first shoulder
Internal Drive Style:
High-torque Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32 Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp
6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1603 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-00-623-0839

Shoulder Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

