## NSN 5305-00-623-1204

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-623-1204

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 2.016 inches and 2.046 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130
Surface Treatment:
Paint head
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-623-1204

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

