Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-623-8226

Thread Clas	s:
2a	
Thread Dire	ction:
Right-hand	
Thread Leng	-
0.375 inches	
Fastener Le	
1.194 inches	
Head Style:	
Pan no. 2	
Head Diame	ter:
0.281 inches	
Head Heigh	t:
Between 0.0	71 inches and 0.080 inches
First Diame	ter From Head:
0.100 inches	i de la construcción de la constru
Distance Fre	om Largest Bearing Surface Of Head To End Of First Diameter:
0.750 inches	i de la construcción de la constru
Internal Driv	/e Style:
Slot	
Thread Dian	neter:
0.138 inches	i de la construcción de la constru
Thready Qty	/ Per Inch (tpi):
32	
Externally R	elieved Body Diameter Quantity:
1	
Special Fea	tures:
Cone point 9	0 degrees of angle 0.069 in. Lg
Material:	
Steel comp 3	303
Material Spe	ecification:
Qq-s-764 co	nd a federal specification single material response
Surface Tre	atment:
Passivate	
Thread Seri	es Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	

NSN 5305-00-623-8226

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

