NSN 5305-00-623-8280

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-623-8280 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** Between 0.816 inches and 0.848 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.360 inches and 0.391 inches **Head Height:** Between 0.172 inches and 0.203 inches **First Diameter From Head:** Between 0.297 inches and 0.328 inches **Second Diameter From Head:** Between 0.109 inches and 0.119 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.469 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Cone point 90 degrees of angle Material: Steel comp 1212 **Material Specification:** Astm a108 assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-623-8280

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0