## NSN 5305-00-625-1800

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-625-1800 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.451 inches **Fastener Length:** Between 0.516 inches and 0.561 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.496 inches and 0.510 inches **Head Height:** 0.076 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Features Provided:** O ring and washer Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4037 **Screw Material Specification:** Sae assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Special Features:** Polytetrafluoroethylene washer and an o-ring **Thread Series Designator:** Unf

Shelf Life: N/a **Unit Of Measure:** 

## NSN 5305-00-625-1800

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0